PT2RSE

TOUCH SCREEN LCD DISPLAY

Panel Type	12.1” TFT Active Matrix Panel
Max. Resolution	800 × 600 SVGA@75Hz
Pixel Pitch	0.3075(H) × 0.3075(V)
Contrast Ratio	400:1
Brightness	185 cd/m2
Display Area	245.76 × 184.32 mm
Response Time	16 ms (Typ.)
Display Colors	262K
Viewing Angle	90°(H)/50°(V)
Signal Connector	VGA
VGA Input Signal	RGB Analog 0.7V Peak to Peak
OSD Control	Power Switch, Menu, Select (+, -), Auto
Operation Temperature	0° ~ 50° C
Storage Temperature	-20° ~ 60° C
Power Consumption	25 W
Power Supply	External Power Adapter
Safely & EMI	CE, FCC, TUV-GS, UL Compliant
Touch screen	Resistive; RS232
Dimension	(With Stand)304.1 x 267.46-x 104.97 (mm) 11.97” x 10.53” x 4.13” (Without Stand)304.1 x 219.1 x 104.97 11.97” x 8.64” x 4.13”
Weight	5.4 lbs (2.5 kg)

ACCUVIEW INC•
Tel: 800.275.4255 Fax: 201.440.5655 Address: 40C Cotters Lane, Suite F, East Brunswick NJ 08816 Email: sales@accuview.com
*Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 Accuview Inc. All rights reserved.